## BRAIDED FLEXIBLES

- Design flexibility
- Ease of maintenance and replacement
- Minimal waste (with no pipes to cut to waste).
- Reduction in noise and an allowance for expansion

#### **Connection Applications**

Braided Flexibles help keep costs to a minimum. They are ideal for overcoming space restrictions and for connecting non aligned components, without the need for brazed joints and bends, giving:

- Design flexibility.
- Ease of maintenance and replacement.
- Minimal wastage (with no pipes to cut to length).
- Reduction in noise and an allowance for expansion.

Ferrier Pumps stock standard Braided

- Various construction materials
- Insulated versions

Typical applications include:

- Fan Coil Units
- Air Handling Units.
- Small pumps.
- Isolation of pipework.
- Connection to sanitation equipment.
- Final connections of gas appliances.

Call our technical sales advisors, who can assist

Flexibles in several s order:	,	you with selecting the correct Braided Flexible for your application.						
Available in the following standard sizes								
Diameters (BSP)	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"		
Lengths 300mm		45	450mm		600mm			

End connectors in brass or bichromated steel	DIA.	
Crimped ferrules -		$\top$
Outer braiding in stainless or galvanised steel wire		
Synthetic elastomer —		LENGTH
* At operating temp	ale rump adaptor perature of 110	)oC

ПΛ

### **Pressure Rating Table**

DIMENSIONS	Connector	1/2"	3/4"	1"	1 1/4"	1 /1/2"	2"
	Internal Diameter	15	20	26	32	40	50
	External Diameter	22	28	35	43	53	67
	Passage at the connectors	12	17	22	28	35	43
*OPERATING PRESSURE (bar)	Galvanised steel braid	15	12	10	8	7	-
	Stainless steel braid	20	17	13	11	8	7
BURSTING PRESSURE	Galvanised steel braid	75	60	50	40	35	-
(bar)	Stainless steel	100	85	65	55	40	37

**Discuss your** application requirements when you order to ensure satisfactory performance

## **Edinburgh Depot**

Burlington Street, Leith Edinburgh, EH6 5JL Tel: 0131 553 4001 edinburgh@ferrierpumps.co.uk

## **Glasgow Depot**

71 Cumbernauld Road, Dennistoun Glasgow, G31 2SN Tel: 0141 554 3454 glasgow@ferrierpumps.co.uk

## **Aberdeen Depot**

Units 4 & 5, Barclayhill Place Portlethen, Aberdeen ABI2 4PF Tel: 01224 782022 aberdeen@ferrierpumps.co.uk

# FLEXIBLE BELLOWS

### (UNTIED)

- Suitable for both LPHW and chilled water
- Corrosion resistant and maintenance free
- Potable water grade Bellows available
- WRAS approved product, no. 1507334



#### Flexible Bellows

United Flexible Bellows are moulded and fabricated units, eliminating pipe line noise transmission.

Available with standard and non standard flange drilling, they cater for a wide range of Building Services or Industrial applications including:

- Chilled Water
- LPHW
- Pressures up to 16 bar
- Temperatures up to 85 degrees centigrade

Manufactured to a high standard, the units are:


- 100% leak proof.
- Corrosion resistant.
- Maintenance free.


Discount of a state of Allegarity Ma

They can be incorporated in a variety of designs to solve noise problems and isolate vibration, making them popular additions at pump suction/discharge connections.

Standard flange drilling conforms to BS4505 NP6 or NP16

Discuss alternative drilling requirements with our Technical Sales Advisors





	Component Materials				
Item	tem Part Material				
1	Body	Heat Resisting Rubber			
2	Body	Nylon Tyre Cord			
3	Wire	Hard Steel Wire			
4	Flange	Mild Steel			

Maximum Working Pressure @ 50 C = 7 bar

Maximum Working Pressure @ 85 C = 3.5 bar
(Typical application values, check with our sales advisors)

Nominal Diameter		Natural Installed Length Allowable Movements from Natural Length					Pressures	
		mm	Axial Compression (mm)	Axial Extension (mm)	Lateral Deflection (mm)	Angular Deflection (mm)	Positive P.S.I.G at Deg C	Vacuum (mm)
Inch	mm	125	10	5	10	10	225	660
1 1/4"	32	125	10	5	10	10	225	660
1 1/2"	40	125	10	5	10	10	225	660
2"	50	125	10	5	10	10	225	660
2 1/2"	65	125	10	5	10	10	225	660
3"	80	125	10	5	10	10	225	660
4"	100	125	10	5	10	10	225	660
5"	125	125	10	5	10	10	225	660
6"	150	125	7	5	7	7	225	660

## **Edinburgh Depot**

Burlington Street, Leith Edinburgh, EH6 5JL **Tel:** 0131 553 4001 edinburgh@ferrierpumps.co.uk

## **Glasgow Depot**

71 Cumbernauld Road, Dennistoun Glasgow, G31 2SN **Tel:** 0141 554 3454 glasgow@ferrierpumps.co.uk

### **Aberdeen Depot**

Units 4 & 5, Barclayhill Place Portlethen, Aberdeen AB12 4PF **Tel:** 01224 782022 aberdeen@ferrierpumps.co.uk